



Model 180 - Model 501 - Model 601

Le ROCKLINIZER guarantees a solid prevention as well as a reduced and more efficient maintenance of your production equipments.

- The applicator pistol ROCKLINIZER deposes from 0 to 100 microns in only one application.
- The deposit is controlled electronically and automatically according to the settings defined by the user.
- The electrodes ROCKLINIZER apply uniformly the wanted coat thanks to a sparks process.
- The material does not suffer of molecular structure alterations.
- No heating or soak, the treated areas are more resistant than the actual metal.
- Le ROCKLINIZER applies to all kinds of steel.



Model 180



Model 501



Model 601

MAIN ADVANTAGES

- Total control over the thickness to be applied
- Intensity setting in accordance to your needs
- Constant restoration of the nominal size
- No heating applied
- No deformation
- No flakes
- Protection of the cutting crests

LE ROCKLINIZER IS A SOURCE OF ECONOMIES!

Thanks to the ROCKLINIZER, you will be able to economise:

- ➔ Raw materials
- ➔ Energy
- ➔ Time



73 rue de la Faïencerie 33 300 BORDEAUX – FRANCE
Tél. (+33) 05 56 29 51 60 // Fax (+33) 05 56 29 51 69
e-mail : sstfrance@wanadoo.fr
www.sstmicrowelding.com





Model 180 - Model 501 - Model 601

Models' Features

	MODEL 180	MODEL 501	MODEL 601
PERFORMANCES	-deposits from 00 to + 10~15 microns (approx.)	- deposits from 00 to + 0.002''	- deposits from 00 to 0.004''
WEIGHT	11.8 Kg	14.5 Kg	22.3 Kg
SPECIFICITIES	- model possessing 9 unloading positions	- the deposit is automatically or manually applied when the electrode is in contact with the concerned object	- the deposit is automatically or manually applied when the electrode is in contact with the concerned object

Consumables & Accessories

Carbide Electrode

Tungstene		Titane	
Diameter	Length	Diameter	Length
5,1 mm	51 mm	5,1 mm	51 mm
3,6 mm	51 mm	3,6 mm	51 mm
2,6 mm	51 mm	2,6 mm	51 mm
1,9 mm	51 mm	1,9 mm	51 mm
1,0 mm	51 mm		
0,75 mm	51 mm		

Designation	Diameter	Length
ROCKHARD for applications with model 601	3,2 mm	102 mm
STEEL ELECTRODE 140 kg PLASTIC RELOADING pack of 10 electrodes	2 mm	
STEEL ELECTRODE 180 kg Co	4 mm	51 mm
STEEL ELECTRODE 180 kg Ni	4 mm	51 mm
NEW PISTOL		
PISTOL IN STANDARD EXCHANGE		



73 rue de la Faïencerie 33 300 BORDEAUX –
FRANCE
Tél. (+33) 05 56 29 51 60 // Fax (+33) 05 56 29 51
69
e-mail : sstfrance@wanadoo.fr
www.sstmicrowelding.com

